

IN THE CLAIMS

Please amend the claims to read as indicated below.

1. (currently amended) A method comprising:

~~connectingsituating~~ a configuration device ~~to at an coupling~~ installation location of an intelligent unit in a system,

wherein the configuration device ~~is configured for coupling to an intelligent unit, and is not a component of said intelligent unit, and~~

wherein the configuration device is part of a permanent wiring, to which the intelligent unit can be coupled, or is associated with a connecting device disposed at the coupling location for connection of the intelligent unit; and

storing configuration data in the configuration device, ~~pertaining to the installation location;~~

wherein the configuration data comprises behaviour or function description data, which is location-based in each case for the intelligent unit, and

wherein the configuration data ~~is~~ can be transmitted from the configuration device to a logic device that processes the configuration data for configuration of the intelligent unit.

2. (currently amended) The method as claimed in claim 1, further comprising the following steps:

provisioning the intelligent unit with the logic device;

coupling the intelligent unit to the configuration device; and

transmitting the configuration data from the configuration device to the logic device.

3. (previously presented) The method as claimed in claim 1, further comprising:

transmitting data from the intelligent unit to the configuration device; and

storing the data from the intelligent unit in the configuration device.

4. (previously presented) The method as claimed in claim 1, further comprising matching data between the intelligent unit and the configuration device.

5. (previously presented) The method as claimed in claim 1, wherein the intelligent unit is in a network.

6. (currently amended) The method as claimed in claim 1, wherein the storing and/or the transmitting of the configuration data is carried out as a single step, or as a repeatable step.

7. (currently amended) The method as claimed in claim 1, wherein the storing and/or the transmitting of the configuration data is performed securely.

8. (currently amended) An apparatus, comprising:

a configuration device ~~associated~~situated at a coupling~~installation~~ location of an intelligent unit in a system; ~~and having configuration data stored therein pertaining to the installation location,~~

wherein the configuration device ~~is configured for coupling to an intelligent unit, and is not a component of said intelligent unit, and~~

wherein the configuration device is part of a permanent wiring, to which the intelligent unit can be coupled, or is associated with a connecting device disposed at the coupling location for connection of the intelligent unit, and

wherein the configuration data comprises behaviour or function description data, which is location-based in each case for the intelligent unit, and

wherein the configuration data is transmittable from the configuration device to a logic device that processes the configuration data for configuration of the intelligent unit.

9. (canceled)

10. (currently amended) The apparatus as claimed in claim 8,

~~wherein the configuration device can be associated with a defined application and/or a defined location of the intelligent unit, and~~

wherein the configuration device can be connected to the logic device for processing of the configuration data for configuration of the intelligent unit in such a way that the configuration data can be transmitted at least from the configuration device to the logic device.

11. (currently amended) The apparatus as claimed in claim 8,

wherein the intelligent unit has the logic device associated therewith for processing of the configuration data for configuration of the intelligent unit, and

wherein the intelligent unit can be connected to the configuration device in such a way that the configuration data can be transmitted at least from the configuration device to the logic device for configuration adaptation of the intelligent unit ~~to the application and/or the location~~.

12. (previously presented) The apparatus as claimed in claims 8,

wherein the intelligent unit is within a network.

13. (previously presented) The apparatus as claimed in claim 8,

wherein the intelligent unit has a system component.

14. (currently amended) The apparatus as claimed in claim 8,

wherein the configuration data comprises an address; and/or a component identification; ~~configuration data and/or data for configuration.~~

15. (currently amended) The apparatus as claimed in claim 8,

wherein the logic device transmits ~~the~~ data to the configuration device.

16. (currently amended) The apparatus as claimed in claim 8,

wherein the configuration device receives and stores ~~the~~ data from the logic device.

17. (canceled)

18. (canceled)

19. (canceled)

20. (previously presented) The apparatus as claimed in claim 8, wherein the configuration device is for storage, reading and/or processing of further data.

21. (previously presented) The apparatus as claimed in claim 8, wherein the data of the configuration device is variable, readable and/or processable by remote control and/or externally.

22. (previously presented) The apparatus as claimed in claim 8, wherein the configuration device and the intelligent unit have complementary means for provision of a unidirectional and/or bidirectional data transmission connection.

23. (previously presented) The apparatus as claimed in claim 8, wherein the configuration device is equipment for an automation system.

24. (previously presented) The apparatus as claimed claim 8, wherein the configuration device and/or the logic device have hardware and/or software elements.

25. (previously presented) The apparatus as claimed in claim 8, wherein the logic device is part of the configuration device or part of a further device which can be connected to the configuration device.

26. (canceled)

27. (previously presented) A system having at least one apparatus as claimed in claim 8.

28. (previously presented) The system as claimed in claim 27, wherein the system is adapted for operation of an automation system.

29. (cancelled)

30. (canceled).

31. (currently amended) The method of claim 1, wherein said configuration data comprises an address; and/or a component identification; ~~configuration data and/or data for configuration.~~

32. (previously presented) The apparatus of claim 22, wherein the complementary means for provision of a unidirectional and/or bidirectional data transmission connection comprises a component selected from the group consisting of a screw-in connector, a plug-in connector, a contact-based connector, an optical connector and a radio connector.